



# 197Sa

## 19" TFT MONITOR

### SPECIFICATIONS




Energy Star - Lable for all Energy Efficient Office equipments



The AOC Product is TCO 03 tested



ALL AOC products are RoHS compliant



All AOC TFTs' have the possibility to use the VESA Wall Mount devices



Dynamic Contrast Ratio increases the contrast between black and white over 3000:1; DCR is perfect for watching movie and video content.



Shows the Response time for the products



Colours FCR 8-bit panel can display 16.7M colours, more vibrant than traditional 6-bit panel



Eco Mode

<b>Panel</b>	19" (48 cm) TFT Active Matrix LCD, Diagonal Hard Coating (3H), Anti-glare Treatment
<b>Design Line</b>	Value
<b>Pixel / Dot Pitch</b>	0.294mm x 0.294mm
<b>Viewable Image Size (Diagonal)</b>	19"
<b>Display Area</b>	376mm x 301mm
<b>Brightness</b>	300 cd/m <sup>2</sup> (typ)
<b>Contrast Ratio</b>	2000:1 (DCR)
<b>Typ. Response Time (tr+tf)</b>	5ms
<b>Viewing Angle</b>	CR=10: 160/160 Degrees

<b>Compatibility</b>	VESA, VGA, SVGA, XGA, SXGA, Mac@Equipped With VGA Port
<b>Scanning Frequency</b>	Horizontal: 30K~83KHz Vertical: 55~75 Hz
<b>Pixel Frequency</b>	135 MHz
<b>Maximum Resolution</b>	1280x1024@75Hz (Analogue) 1280x1024@75Hz (DVI-D)
<b>Recommended Resolution</b>	1280x1024@60Hz
<b>Resolution Supported</b>	640x400@70Hz, 720x400@70Hz, 832x624@75, 640x480@60/67/72/75Hz, 800x600@56/60/72/75Hz, 1024x768@60/70/75Hz, 1280x1024@60/75Hz
<b>Colours</b>	16.7 M
<b>Signal Input</b>	Analogue: Video: 0.7Vp-p, RGB analogue, Separate Sync: TTL Level, H/V Sync: Positive / Negative

<b>Connectors</b>	Analogue RGB Signal: 15-pin D-sub Male (Attached), Power: 3-pin Plug (CEE22)
-------------------	---

<b>Power Source</b>	Power Input: Universal 100~240VAC, 50/60Hz
---------------------	---

<b>Power Consumption</b>	37 Watts (Max)
<b>Plug &amp; Play</b>	DDC1/2B/CI

<b>EPA ENERGY STAR ®</b>	
<b>User Control</b>	Auto Adjust, Menu, On/Off, Eco/Left, Vol/Right
<b>Function</b>	Brightness, Contrast, Eco Mode, Gamma(1,2,3), DCR, Focus, Clock, H/V Position, Color Temperature, Color Boost, Picture Boost, OSD Setup, AUTO Config, Reset, Information

<b>OSD Languages</b>	English, French, Spanish, German, Russian, Italian, Swedish, Polish, Czech
----------------------	--

<b>Speaker</b>	2 x 1Watt, Volume Control, Earphone Output
----------------	---

<b>Emissions Standard</b>	
<b>Regulation</b>	cUL, FCC, CE, TUV/GS, TCO03, Windows Vista

<b>Other Features</b>	VESA 100mm Wall Mountable*, Kensington Security Slot
-----------------------	--

<b>Dimensions (WxHxD)</b>	Monitor: 413x413x216 mm Carton: 482x151x434 mm
<b>Weight</b>	Net: 4.8Kg Gross: 6.3Kg
<b>Loading Qty w/pallet</b>	20' = 504 pcs 40' = 1120 pcs
<b>Warranty</b>	3 Years Parts & Labour
<b>EAN Code</b>	4038986190237

**Note:** Specifications are subject to change without notice. \*Wall mount arm & bracket not included.